





-  柔光片
 -  防眩网
 -  防眩杯(亮银)
 -  防眩杯(哑黑)
 -  防眩杯(白色)
- *可选配件



产品特性

灯具颜色: 金属灰+白色面板
 主体材质: 压铸铝
 光学系统: 透镜+防眩杯
 灯具外观: 金属质感
 投射方向: 垂直0~30°、水平0~355°
 防护等级: IP20 可选配IP44防水组件
 环境温度: -20°~40°
 重量: 121g

产品规格


开孔尺寸: Ø 55mm
 功率: 7W
 光束角度: 15°、24°、36°、60°
 天花厚度: 2mm~25mm
 安装方式: 嵌入式
 吊顶空间: 大于100mm
 防眩角度: 40°

输入电压: 220~240V~50Hz
 输入电流: 33mA
 显指: Ra92
 色温: 2700K、3000K、3500K、4000K
 光通量: 406lm、423lm、452lm、469lm (15°)
 449lm、468lm、501lm、519lm (24°)
 480lm、500lm、536lm、556lm (36°)
 418lm、435lm、465lm、483lm (60°)

以下可调光款为可控硅调光; 0~10V调光:T改为M

2700K
 TSF6055W07-TB2715
 TSF6055W07-NB2715

可调光
 不可调光

 15°

h(m)	D(cm)	average (lx)	center (lx)
1.0	29	2543	3650
2.0	57	636	913
3.0	86	283	406
4.0	114	159	228

3000K
 TSF6055W07-TB3015
 TSF6055W07-NB3015

可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	29	2649	3802
2.0	57	662	951
3.0	86	294	423
4.0	114	166	238

3500K
 TSF6055W07-TB3515
 TSF6055W07-NB3515


可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	29	2834	4068
2.0	57	709	1017
3.0	86	315	452
4.0	114	177	254

4000K
 TSF6055W07-TB4015
 TSF6055W07-NB4015


可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	29	2940	4220
2.0	57	735	1055
3.0	86	327	469
4.0	114	184	264



2700K
 TSF6055W07-TB2724
 TSF6055W07-NB2724

可调光
 不可调光

 24°

h(m)	D(cm)	average (lx)	center (lx)
1.0	39	1610	2354
2.0	79	403	589
3.0	118	179	262
4.0	157	101	147

3000K
 TSF6055W07-TB3024
 TSF6055W07-NB3024

可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	39	1677	2452
2.0	79	419	613
3.0	118	186	273
4.0	157	105	153

3500K
 TSF6055W07-TB3524
 TSF6055W07-NB3524


可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	39	1795	2624
2.0	79	449	656
3.0	118	199	292
4.0	157	112	164

4000K
 TSF6055W07-TB4024
 TSF6055W07-NB4024


可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	39	1862	2722
2.0	79	466	681
3.0	118	207	302
4.0	157	116	170



2700K
 TSF6055W07-TB2736
 TSF6055W07-NB2736

可调光
 不可调光

 36°

h(m)	D(cm)	average (lx)	center (lx)
1.0	62	795	1217
2.0	123	199	304
3.0	184	88	135
4.0	246	50	76

3000K
 TSF6055W07-TB3036
 TSF6055W07-NB3036

可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	62	828	1268
2.0	123	207	317
3.0	184	92	141
4.0	246	52	79

3500K
 TSF6055W07-TB3536
 TSF6055W07-NB3536


可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	62	886	1357
2.0	123	222	339
3.0	184	98	151
4.0	246	55	85

4000K
 TSF6055W07-TB4036
 TSF6055W07-NB4036


可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	62	919	1408
2.0	123	230	352
3.0	184	102	156
4.0	246	57	88



2700K
 TSF6055W07-TB2760
 TSF6055W07-NB2760

可调光
 不可调光

 60°

h(m)	D(cm)	average (lx)	center (lx)
1.0	91	402	606
2.0	181	101	152
3.0	271	45	67
4.0	362	25	38

3000K
 TSF6055W07-TB3060
 TSF6055W07-NB3060

可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	91	419	631
2.0	181	105	158
3.0	271	47	70
4.0	362	26	40

3500K
 TSF6055W07-TB3560
 TSF6055W07-NB3560

可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	91	448	675
2.0	181	112	169
3.0	271	50	75
4.0	362	28	42

4000K
 TSF6055W07-TB4060
 TSF6055W07-NB4060

可调光
 不可调光

h(m)	D(cm)	average (lx)	center (lx)
1.0	91	465	701
2.0	181	116	175
3.0	271	52	78
4.0	362	29	44

