



防眩天花灯(Ø75)



-  柔光片
-  防眩网
-  防眩杯(亮银)
-  防眩杯(哑黑)
-  防眩杯(白色)

*可选配件



产品特性



















灯具颜色: 金属灰+白色面板
 主体材质: 压铸铝
 光学系统: 透镜+防眩杯
 灯具外观: 金属质感
 投射方向: 垂直0~30°、水平0~355°
 防护等级: IP20 可选配IP44防水组件
 环境温度: -20°~40°
 重量: 263g

产品规格

开孔尺寸: Ø 75mm
 功率: 7W
 光束角度: 15°、24°、36°、60°
 天花厚度: 2mm~25mm
 安装方式: 嵌入式
 吊顶空间: 大于115mm
 防眩角度: 40°

输入电压: 220~240V~50Hz
 输入电流: 33mA
 显指: Ra92
 色温: 2700K、3000K、3500K、4000K
 光通量: 406lm、423lm、452lm、469lm (15°)
 449lm、468lm、501lm、519lm (24°)
 480lm、500lm、536lm、556lm (36°)
 418lm、435lm、465lm、483lm (60°)

以下可调光款为可控硅调光; 0~10V调光:T改为M

色温	可调光	不可调光	光束角	h(m)	D(cm)	average (lx)	center (lx)	光通量分布图
2700K	☑	TSF6075W07-TB2715		1.0	29	2543	3650	
		2.0		57	636	913		
	3.0	86		283	406			
	4.0	114		159	228			
3000K	☑	TSF6075W07-TB3015		1.0	29	2649	3802	
		2.0		57	662	951		
	3.0	86		294	423			
	4.0	114		166	238			
3500K	☑	TSF6075W07-TB3515		1.0	29	2834	4068	
		2.0		57	709	1017		
	3.0	86		315	452			
	4.0	114		177	254			
4000K	☑	TSF6075W07-TB4015		1.0	29	2940	4220	
		2.0		57	735	1055		
	3.0	86		327	469			
	4.0	114		184	264			
2700K	☑	TSF6075W07-TB2724		1.0	39	1610	2354	
		2.0		79	403	589		
	3.0	118		179	262			
	4.0	157		101	147			
3000K	☑	TSF6075W07-TB3024		1.0	39	1677	2452	
		2.0		79	419	613		
	3.0	118		186	273			
	4.0	157		105	153			
3500K	☑	TSF6075W07-TB3524		1.0	39	1795	2624	
		2.0		79	449	656		
	3.0	118		199	292			
	4.0	157		112	164			
4000K	☑	TSF6075W07-TB4024		1.0	39	1862	2722	
		2.0		79	466	681		
	3.0	118		207	302			
	4.0	157		116	170			
2700K	☑	TSF6075W07-TB2736		1.0	62	795	1217	
		2.0		123	199	304		
	3.0	184		88	135			
	4.0	246		50	76			
3000K	☑	TSF6075W07-TB3036		1.0	62	828	1268	
		2.0		123	207	317		
	3.0	184		92	141			
	4.0	246		52	79			
3500K	☑	TSF6075W07-TB3536		1.0	62	886	1357	
		2.0		123	222	339		
	3.0	184		98	151			
	4.0	246		55	85			
4000K	☑	TSF6075W07-TB4036		1.0	62	919	1408	
		2.0		123	230	352		
	3.0	184		102	156			
	4.0	246		57	88			
2700K	☑	TSF6075W07-TB2760		1.0	91	402	606	
		2.0		181	101	152		
	3.0	271		45	67			
	4.0	362		25	38			
3000K	☑	TSF6075W07-TB3060		1.0	91	419	631	
		2.0		181	105	158		
	3.0	271		47	70			
	4.0	362		26	40			
3500K	☑	TSF6075W07-TB3560		1.0	91	448	675	
		2.0		181	112	169		
	3.0	271		50	75			
	4.0	362		28	42			
4000K	☑	TSF6075W07-TB4060		1.0	91	465	701	
		2.0		181	116	175		
	3.0	271		52	78			
	4.0	362		29	44			